


## Event-Ready LED Video Walls

The Leyard® VVR Series is a family of indoor and outdoor LED video wall displays designed to meet the fast-paced needs of rental & staging, large venue and event applications. Delivering fast assembly and easy access to electronics, Leyard VVR Series LED displays feature magnetically-attachable cabinets with a quick-lock system to support single-person handling.

Leyard VVR Series indoor models are available in 2.5, 3.9, 4.8 and 5.9mm pixel pitches and outdoor models are available in 2.9, 3.9, 4.8, 5.9, 7.8 and 10.4mm pixel pitches. The Leyard VVR Series easily adapts to indoor, outdoor, hanging and floor-mounted installations — creating stunning video walls that visually enhance environments.

# Exceeding Fast-Paced Demands

Leyard VVR Series LED video walls deliver the highest level of display flexibility and set-up ease that is required in rental, staging and flexible-fixed installations and not commonly found in traditional LED video wall displays. Developed specifically for dynamic environments, the Leyard VVR Series is designed for quick, easy installation and teardown, while delivering high performance image quality and reliability.



## DESIGNED FOR FREQUENT SET-UP & TEARDOWN


Leyard VVR Series LED video walls are designed for single-person installation and teardown, reducing the time required for installation, lowering costs while adding a competitive edge.

To assist in single-person installation, the Leyard VVR Series features magnetic points that briefly hold the LED cabinet in place while an installer secures the LED cabinet and finalizes cabling. Leyard VVR Series cabinets also feature an embedded quick-lock system, making it easy and efficient to secure cabinets together.




# EASY-TO-ACCESS SERVICE FEATURES


The Leyard VVR Series features a self-contained LED cabinet design with easily removable modules via front or rear access.



**Front Module Removal with Magnet Tool**  
*Leyard VVR Series Indoor Models*  
2.5, 3.9, 4.8, 5.9mm



**Rear Module Removal with Rotating Latches**  
*Leyard VVR Series Outdoor Models*  
2.9, 3.9, 4.8mm



**Front & Rear Module Removal with Hex Tool**  
*Leyard VVR Series Outdoor Models*  
5.9, 7.8, 10.4mm



## Installation Variety by Design

With the Leyard VVR Series, flexibility and stunning visual performance are at the forefront of product design to meet the fast-paced demands of rental & staging environments and creative flexibility required for fixed installations.

Leyard VVR Series LED video walls easily adapt to various designs, including hanging, stacking, wall-mounted, floor-mounted, attached to traditional and customized frame styles. With a wide range of configurations, the Leyard VVR Series is ideal for applications including concerts, festivals, conferences, public gatherings, tradeshows or exhibitions.

## Visually Stunning In Any Environment

With high brightness, excellent contrast and a wide color gamut, the Leyard VVR Series delivers exceptional image quality to enhance dynamic applications. The Leyard VVR Series is suitable for high ambient light applications with indoor models offering 1000-nit brightness and outdoor models offering high brightness of 5000-nit.

With an IP65 Ingress Protection Rating, the dust-tight enclosure of the Leyard VVR Series' outdoor models works to protect the LED display in harsh outdoor conditions.

## Compact & Reliable Components

The Leyard VVR Series incorporates a rack-mounted video controller that supports resolutions up to 2.3 million pixels and includes control software that delivers a variety of controls and adjustments via a user-friendly interface.

The Leyard VVR Series uses power and signal cables compatible with industry-standards and features a fast and easy twist-lock latching system. All electronics are contained in single compartment on back of cabinet. The electronic compartment is easily removable to quickly access and service all components.

## LEYARD VVR SERIES INDOOR SPECIFICATIONS

| Model                                  | VVRI-2.5                                  | VVRI-3.9                | VVRI-4.8                | VVRI-5.9                |
|--|---|-------------------------|-------------------------|-------------------------|
| Pixel Pitch                            | 2.5mm                                     | 3.91mm                  | 4.81mm                  | 5.95mm                  |
| Resolution                             | 200x200                                   | 128x128                 | 104x104                 | 84x84                   |
| Pixel Density                          | 160000/sq m   14864/sq ft                 | 65536/sq m   6088/sq ft | 43264/sq m   4019/sq ft | 28224/sq m   2622/sq ft |
| Cabinet Size (W x H x D)               | 500 x 500 x 74mm   19.69 x 19.69 x 2.91in |                         |                         |                         |
| Power Consumption, Max (watts)         | 188/Cabinet   750/sq m                    |                         |                         |                         |
| Line Voltage                           | 100~240V AC, 50/60Hz                      |                         |                         |                         |
| Cabinet Weight (per display)           | 7kg   15.43lb                             |                         |                         |                         |
| Brightness Max, Calibration On (cd/sq) | 1000                                      |                         |                         |                         |
| Contrast Ratio                         | 8000:1                                    |                         |                         |                         |
| LED Refresh Rate                       | 3000Hz                                    |                         |                         |                         |
| Color Temp, Adjustable (k)             | 3000 - 1000                               |                         |                         |                         |
| Viewing Angle (horizontal & vertical)  | H: 120°   V: 110°                         |                         |                         |                         |
| Service Access                         | Front (limited - module only)             |                         |                         |                         |
| Environment                            | Indoor                                    |                         |                         |                         |
| Operating Temp/ Humidity (°F/C)        | -10° to 40° C   14° to 104° F             |                         |                         |                         |
| Controller                             | S6F Controller                            |                         |                         |                         |

## LEYARD VVR SERIES OUTDOOR SPECIFICATIONS

| Model                                  | VVRO-2.9                                  | VVRO-3.9                  | VVRO-4.8                   | VVRO-5.9                 | VVRO-7.8                 | VVRO-10.4              |
|--|---|---------------------------|----------------------------|--------------------------|--------------------------|------------------------|
| Pixel Pitch                            | 2.97mm                                    | 3.91mm                    | 4.81mm                     | 5.95mm                   | 7.81mm                   | 10.42mm                |
| Resolution                             | 168x168                                   | 128x128                   | 104x104                    | 84x84                    | 64x64                    | 48x48                  |
| Pixel Density                          | 112896/sq m<br>10488/sq ft                | 65536/sq m<br>6088/sq ft  | 43264/sq m<br>4019/sq ft   | 28224/sq m<br>2622/sq ft | 16384/sq m<br>1522/sq ft | 9216/sq m<br>856/sq ft |
| Cabinet Size (W x H x D)               | 500 x 500 x 74mm   19.69 x 19.69 x 2.91in |                           |                            |                          |                          |                        |
| Power Consumption, Max (watts)         | 163 /Cabinet<br>650 /sq m                 | 175 /Cabinet<br>700 /sq m | 188 / Cabinet   750 / sq m |                          |                          |                        |
| Line Voltage                           | 100~240V AC, 50/60Hz                      |                           |                            |                          |                          |                        |
| Cabinet Weight (per display)           | 7.5kg   16.53lb                           |                           |                            |                          |                          |                        |
| Brightness Max, Calibration On (cd/sq) | 5000                                      |                           |                            |                          |                          |                        |
| Contrast Ratio                         | 6000:1                                    |                           |                            |                          |                          |                        |
| LED Refresh Rate                       | 3000Hz                                    |                           |                            |                          |                          |                        |
| Color Temp, Adjustable (k)             | 3000 - 1000                               |                           |                            |                          |                          |                        |
| Viewing Angle (horizontal & vertical)  | H: 120°, V: 110°                          |                           |                            |                          |                          |                        |
| Service Access                         | Rear                                      |                           |                            | Rear   Front (modules)   |                          |                        |
| Environment                            | Outdoor                                   |                           |                            |                          |                          |                        |
| Protection                             | IP65                                      |                           |                            |                          |                          |                        |
| Operating Temp/ Humidity (°F/C)        | -20° to 40° C   -4° to 104° F             |                           |                            |                          |                          |                        |
| Controller                             | S6F Controller                            |                           |                            |                          |                          |                        |

[www.leyard.com](http://www.leyard.com) | [www.planar.com](http://www.planar.com)

North America  
1-866-475-2627  
sales@leyardgroup.com

EMEA  
+421-907-775-941  
sales.emea@leyardgroup.com

APAC  
+852 2326 0228  
info.asia@leyardgroup.com

Japan  
+81-3-6915-2768  
info.japan@leyardgroup.com

Latin America  
+55-41-3059-5100  
info.brazil@leyardgroup.com