

Christie HS Series

4K7-HS / 4K10-HS

Enterprise venues and boardrooms

Entertainment venues

Fixed installation

Houses of worship

Hotels

Live events and conferences

Rental and staging

Trade shows and exhibitions



High-performance, low-cost 4K projection

The Christie® 4K7-HS and 4K10-HS combine the cost-savings of 1DLP® technology, the long operational life of laser, and the image quality of 4K UHD resolution. The result is a pair of high-performance 7,000 and 10,000 lumen, 4K UHD, HDR10 compatible laser projectors that won't blow your budget.

What makes the 4K7-HS and 4K10-HS outperform the competition is the enhanced color performance thanks to the patented Christie BoldColor Technology. Colors are vibrant and natural and with the added fidelity of 4K UHD resolution, visuals pop off the screen.

These projectors feature industry-leading, built-in Christie Twist™ for quicker and easier multi-projector setups. For even more flexibility, the 4K7-HS and 4K10-HS have two expandable option card slots which can accommodate cards such as the Christie Terra SDVoE input card; 12G SDI input cards; and HDBaseT input cards. Plus, with HDMI 2.0, DisplayPort 1.2 inputs, you can feed the projector 4K60Hz content over a single HDMI or DisplayPort cable for simplified setup and cable routing.

CHRISTIE®

		Christie 4K10-HS	Christie 4K7-HS
Image	brightness (lumens)	• 11,000 ISO • 10,000 ANSI	• 7600 ISO • 7000 ANSI
	color wheel	• 4 segment (RGBY) - 2X speed	
	contrast (nominal)	• Full on/off (Christie RealBlack enabled): 2,000,000:1 • Dynamic contrast: 5000:1 • Full on/off (Christie RealBlack disabled): 1200:1 • ANSI 250:1	
Display technology	type	• 1 x 0.66" DMD	
	resolution	• 4K UHD (8.3MP); 2716x1528 (WQXGA+) DMD (native); 16:9	
Illumination	type	• Laser phosphor with Christie BoldColor Technology	
	typical lifetime	• 20,000 hrs to 50%	
Signal inputs	standard	• HDMI x 2 (HDMI 2.0b, HDCP 2.1 Compliant) • DVI-D x 1 (digital only) • DisplayPort x 1 (versions 1.2) • USB x 1 (Type A) • Wi-Fi® dongle (optional) • HDBaseT (RJ45 x 1) Standard on 4K10-HS and optional on 4K7-HS	
	optional	• Terra SDVoE (optional input card) • 12G SDI (optional input card) • Note: HDBaseT is standard on 4K10-HS and optional on 4K7-HS but occupies 1 of the 2 optional input slots	
	signals	• Standard video signals up to 4096 x 2160 @ 60Hz (over a single cable; HDMI 2.0 or DP 1.2) • Horizontal and vertical scaling while maintaining aspect ratio, all inputs	
	3D and 2D HFR	• HDMI 1.4, HDBaseT - frame packed, top/bottom, side-by-side (up to 120Hz output) • Optional signal input up to 1920 x 1200 @ 120Hz over HDMI, DP and DVI • 3D sync in (BNC) - for genlocking projectors • 3D sync out (BNC) - for genlocking projectors, or controlling emitter or polarizer	
	pixel clock	• Maximum input pixel rate 600 Mpix/s (supports 4096 x 2160 @ 60Hz / 3840 x 2160 @ 60Hz over HDMI & DP) • Minimum input pixel rate 27 Mpix/s (supports 480i @ 60Hz & 576i @ 50Hz)	
	scan rates	• Horizontal: 15kHz to 91kHz • Vertical: 24Hz to 85Hz	
	Signal outputs	monitor out (loop-through)	• 3GSDI x 1 (BNC) • DVI-D x 1 (Digital out)
Control and networking	• RS-232 in • Control via HDBaseT • Ethernet (10/100) RJ45 • Built-in backlit keypad • Wired remote control (3.5mm stereo) • Loop out available for daisy chaining		
	• Boresight adjustable • Motorized horizontal and vertical lens offset (memory available) • Motorized zoom and focus adjustment (memory available for full ILS lenses)		
Lenses	mount type	• Boresight adjustable • Motorized horizontal and vertical lens offset (memory available) • Motorized zoom and focus adjustment (memory available for full ILS lenses)	
	lens options	• 1.20-1.73:1 zoom lens (full ILS) • 1.7-2.12:1 zoom lens (full ILS) • 2.12-2.83:1 zoom lens (full ILS) • 2.83-5.66:1 zoom lens (full ILS) • 5.66-10.18:1 zoom lens (full ILS)	
	offsets for all ILS lenses	• ±140% Vertical • ±60% Horizontal	
Accessories	standard	• IR remote w/wired remote jack (wire not included) • AC line cord for projector head • User manual	
	optional	• Christie One Rigging Frame • 1DWUSB-BGN (wireless dongle for video and control) • Christie One Mount Plus • One Mount Extender Rod • Replacement remote control • One Mount Rigging Kit (used with One Mount, One Mount Plus and/or One Mount Extender Rod)	
Power requirements	operating voltage	• Normal: 100-240 VAC @ 50/60Hz	
	power consumption	• Maximum power consumption: 1070W • Eco1 mode (80%): 865W • Eco2 mode (50%): 540W	
	operating current	• Normal mode: 9.0A ±15% (120 VAC), 4.8A ±15% (220 VAC) • Eco1 mode: 7.2A ±15% (120 VAC), 3.9A ±15% (220 VAC) • Eco2 mode: 4.5A ±15% (120 VAC), 2.45A ±15% (220 VAC)	
	dissipation	• Normal mode: 3651 BTU/hr • Eco1 mode: 2951 BTU/hr • Eco2 mode: 1842 BTU/hr	
Audible noise	• Typical: 39dBA • Eco mode: 33dBA		
Physical	size	• (LxWxH) 23.6 x 20.5 x 8.4" (600 x 520 x 214mm) w/o feet	
	shipping size	• (L xWxH) 35.6 x 29.9 x 14.8" (905 x 760 x 365mm)	
	weight (w/o lens)	• 79.4lbs (36kg)	
	shipping weight	• 99.2lbs (45kg)	
Operating environment	temperature	• 32-104°F (0-40°C)	
	humidity	• 0-85% non-condensing	
Regulatory	• Contact Christie for the timing of certifications: UL/CSA/IEC 60950-1, FCC Class A, CE, FDA, CCC, KC, PSE, CU, SABS, BIS, VCCI, RCM, Ukr, TER, SASO • This product conforms to all relevant European directives, standards, safety, health and environmental concerns • RoHS, REACH, WEEE		
Warranty	• Three years parts and labor on the projector • Three years or 15,000 hours parts and labor on the illumination system ¹ • Contact an authorized Christie representative for full details of our limited warranty		

¹Please reference Christie Standard Limited Warranty document for details.

Corporate offices

Christie Digital Systems USA, Inc.
Cypress
ph: 714 236 8610
Christie Digital Systems Canada Inc.
Kitchener
ph: 519 744 8005

Worldwide offices

Australia
ph: +61 (0) 7 3624 4888
Brazil
ph: +55 (11) 2548 4753
China (Beijing)
ph: +86 10 6561 0240
China (Shanghai)
ph: +86 21 6030 0500
Colombia
ph: +57 (318) 447 3179
Eastern Europe
ph: +36 (0)1 47 48 138

France
ph: +33 (0) 1 41 21 44 04
Germany (Cologne)
ph: +49 221 99 512-0
Germany (Mönchengladbach)
ph: +49 2161 566200
India
ph: +91 (080) 6708 9999
Japan
ph: +81 3 3599 7481
Mexico
ph: +52 55 4744 1790

Republic of South Africa
ph: +27 11 251 0000
Singapore
ph: +65 6877 8737
South Korea
ph: +82 2 702 1601
Spain
ph: +34 91 633 9990
United Arab Emirates
ph: +971 (0) 4 503 6800
United Kingdom
ph: +44 (0) 118 977 8000

United States (Arizona)
ph: 602 943 5700
United States (New York)
ph: 646 779 2014

**Independent sales
consultant offices**

Italy
ph: +39 (0) 2 9902 1161
Russia
ph: +7 (495) 930 8961



For the most current specification information, please visit www.christiedigital.com

Copyright 2018 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
Printed in Canada on recycled paper. 4743 Nov 18

CHRISTIE®